

**Performance**

Tipping load (ISO 14397-1)	2049 kg
Rated operating capacity (no more than 35% of Tipping Load)	717 kg
Pump capacity	63.00 L/min
System relief at quick couplers	22.4-23.1 MPa
Max. travel speed	10.0 km/h
Max. travel speed (high range – optional)	14.4 km/h

**Engine**

Make / Model	Bobcat 2.4L, 97/68 EC Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM (ISO 14396)	41.0 kW
Torque at 1800 RPM (ISO 14396)	204.2 Nm
Number of cylinders	4
Displacement	2393 cm <sup>3</sup>
Fuel tank	64.90 L

**Weights**

Operating weight	2961 kg
Shipping weight	2665 kg
Ground pressure	34.00 kPa

**Controls**

Vehicle steering	Direction and speed controlled by two hand levers or optional joysticks
Loader hydraulics tilt and lift	Separate foot pedals or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

**Drive System**

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

**Standard Features**

Bobcat Interlock Control System (BICS)	Cushioned lift and tilt cylinders
Parking brake	Lift arm support
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port <sup>1</sup>	Engine/hydraulics system shutdown
Noise reduction kit	Spark Arrester
Operating lights, front and rear	Automatically activated glow plugs
Deluxe instrument panel	Electrically activated proportional front auxiliary hydraulics
Keyless start with password capability	Auxiliary hydraulics: variable flow/maximum flow
Suspension seat	Machine IQ (telematic)
Seat belt	Manual
Seat bar	CE certification
Tracks — rubber — 300 mm	Warranty: 24 months or 2000 hours (whichever occurs first)
Bob-Tach™ frame	


<sup>1</sup> Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

**Options**

Deluxe pressurized cab with heating	Power Bob-Tach™
Deluxe pressurized cab with HVAC	Radio
Selectable Joystick Controls (SJC)	Strobe
2 Speed	Back-up alarm
Cloth Suspension Seat	Beacon
Attachment control device	Road Option
Hydraulic bucket positioning (including ON/OFF switch)	Custom paint color (min order of 5 units)

**Environmental**

Operator LpA (98/37 & 474-1)	85 dB(A)
Noise level LWA (EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	1.00 ms <sup>-2</sup>
Hand-arm vibration (ISO 5349-1)	2.42 ms <sup>-2</sup>

**Dimensions**


(A)	3604.0 mm	(J)	2781.0 mm
(B)	1976.0 mm	(K)	597.0 mm
(C)	28.0°	(L)	40.0°
(D)	213.0 mm	(M)	91.0°
(E)	1275.0 mm	(N)	1422.0 mm
(F)	2499.0 mm	(N*)	1575.0 mm
(G)	3216.0 mm	(O)	1979.0 mm
(H)	26.0°	(P)	1097.0 mm
(I)	2129.0 mm	(Q)	1397.0 mm

**Attachments**

Angle Brooms	Low Profile Buckets
Auger Accessories	Miscellaneous
Augers	Mowers
Backhoes	Pallet Fork Accessories
Bale Forks	Pallet Forks, Hydraulic
Box Blades	Root Grapples
Breaker Accessories	Scarifiers
Breakers	Scrapers
Brushcat™ Rotary Cutters	Skeleton Buckets
Brush Saws	Snow & Light Material Buckets
Combination Buckets	Buckets
Concrete Mixers	Snow Blades
Construction / Industrial Buckets	Snow Pushers
Diggers	Snow V-Blades
Dozer Blades	Sod Layers
Dumping Hoppers	Soil Conditioners
Fertilizer and Grain Buckets	Spreaders
Flail Cutters	Sweepers
General Purpose (GP)	Tillers
Bucket	Tilt-Tatch
Graders	Utility Forks
Grapples, Industrial	Utility Frames
Landplanes	Vibratory Rollers
Landscape Rakes	Whisker Brooms
Laser Equipment	Wood Chippers